

Spec./Model	Unit	DCW-18 Series	DCW-21 Series	DCW-24 Series
Distance Between Column	mm	1,850	2,150	2,450
Table Length	mm	2,000~5,000	2,000~5,000	3,000~5,000
Table Width	mm	1,500	1,800	2,000
Travel (X/Y/Z)	M	2.2~5.2 / 1.8 / 0.8 (Opt. 1.1)	2.2~5.2 / 2.1 / 0.8 (Opt. 1.1)	3.2~5.2 / 2.4 / 0.8 (Opt. 1.1)
Travel (W)	M	1.0 (Opt. 1.5)		
Spindle Nose To Table	mm	120 ~ 1,920 (90 ~ 2,690)	120 ~ 1,920 (90 ~ 2,690)	120 ~ 1,920 (90 ~ 2,690)
Spindle Motor Output		22 / 26 Kw, 6,000 rpm By Gearbox Hi-Lo Shift		
Tool Magazine	mm	32 Tools / Max. Dia. 125 or 220 (Adjacent Empty)		
Accuracy	mm	Positioning : +/- 0.015 ; Repeatability : +/- 0.003		

Spec./Model	Unit	DCW-28 Series	DCW-32 Series	DCW-36 Series	DCW-42 Series
Distance Between Column	mm	2,850	3,250	3,650	4,250
Table Length	mm	3,000~6,000	3,000~6,000	4,000~6,000	4,000~6,000
Table Width	mm	2,200	2,600	3,000	3,000
Travel (X/Y/Z)	M	3.2~6 / 2.8 / 1.1	3.2~6 / 2.8 / 1.1	4.2~6 / 2.8 / 1.1	4.2~6 / 2.8 / 1.1
Travel (W)	M	1.0 (Opt. 1.5 & 2.0)			
Spindle Nose To Table	mm	145 ~ 2,245 (90 ~ 3,200)	145 ~ 2,245 (90 ~ 3,200)	145 ~ 2,245 (90 ~ 3,200)	145 ~ 2,245 (90 ~ 3,200)
Spindle Motor Output		22 / 26 Kw, 6,000 rpm (Opt. 30 / 37 Kw, 4,500 rpm) By Gearbox Hi-Lo Shift			
Tool Magazine	mm	32 Tools / Max. Dia. 125 or 220 (Adjacent Empty)			
Accuracy	mm	Positioning : +/- 0.015 ; Repeatability : +/- 0.003			